
ARTFELT 9MM SUPER FR PET FELT PANELS

Material	60% Recycled Polyester fiber, 40% virgin fiber
Density	2000g/m ²
Thickness	9mm
Dimension	Available: 1220 x 2440mm/sheets - 1220 x 3055mm/sheets
Formaldehyde Emission	0.00ug/g
Sound Absorption ISO 354:2003	NRC:0.35 (00mm air gap)
Fire Test ASTM E 84-15A	Class A
Environmental	Recycle
Safety	Declare, Red List Free
Panel Care	<p>General Care: Vacuum as needed to remove dirt and dust. Use an air compressor for hard to reach areas.</p> <p>Stain Removal: Blot spills and spots immediately with a clean, soft white dry cloth (do not use paper products). Avoid using solvents or concentrated abrasives to clean ArtFelt. Always test in an inconspicuous area first.</p> <p>On mild stains: Blot ArtFelt with a clean, soft white cloth dampened with a mild solution of soap and warm water. Repeat using only clean water (no soap) to remove soap concentrate. Pat dry with a lint free cloth.</p> <p>On challenging stains: Blot ArtFelt with a clean, soft white cloth dampened with a mixed solution of household bleach and water (10% bleach 90% water). Repeat using only clean water (no bleach) to remove bleach concentration. Pat dry with a lint free cloth.</p>